

WHAT IS CLAIMED IS

1. A communication device which can be freely inserted into and extracted from a slot of a terminal device, wherein

5 a part of said communication device exposed from said terminal device when inserted into said slot is applied a color according to a kind of the communication device.

2. The communication device as set forth in claim 1, comprising

5 a radio unit adapted to a predetermined mobile communication service and applied a color according to a kind of the mobile communication service.

3. The communication device as set forth in claim 1, comprising

5 a radio unit adapted to a predetermined mobile communication service and applied a color according to a kind of the mobile communication service in which part information necessary for the connection to a specific provider is stored.

4. The communication device as set forth in claim 1, said communication device being a communication device to wireless-connect terminal devices and applied

009221 8035460

said color according a transmission rate.

5

5. A set of a plurality of communication devices which can be freely inserted into and extracted from a slot of a terminal device and have radio units adapted to different mobile communication services, wherein

5

a part of said communication device exposed from said terminal device when inserted into said slot is applied a different color for each communication device.

6. A method of conducting authentication between a communication device which can be freely inserted into and extracted from a slot of a terminal device and said terminal device, comprising the steps of:

5

(a) inserting a key module storing the same ID as an ID stored in the communication device into the slot to register the ID stored in the key module at the terminal device, and

10

(b) conducting collation between the terminal device and the communication device inserted into the slot to determine whether the ID stored in the communication device and the ID registered at the terminal device coincide with each other.

7. The authentication method as set forth in claim 6, further comprising the step of,

when the communication device is extracted from

00922T" 80854260

5 the slot after authentication between the terminal
device and the communication device is obtained,
bringing the terminal device to a locked state where
none of input by a user is accepted.

8. The authentication method as set forth in claim 6,
further comprising the steps of:

5 when the communication device is extracted from
the slot after authentication between the terminal
device and the communication device is obtained,
bringing the terminal device to a locked state where
none of input by a user is accepted, and

10 when the communication device is inserted into
the slot of the locked terminal device to obtain
authentication between the terminal device and the
communication device, releasing the terminal device from
the locked state.

9. A method of conducting authentication between a
communication device which can be freely inserted into
and extracted from a slot of a terminal device and said
terminal device, comprising the steps of:

5 (a) inserting a key module storing the same ID
and authentication code as an ID and an authentication
code stored in the communication device and storing a
cryptographic function paired with an inverse
cryptographic function stored in the communication

009227 8085460

10 device into the slot to register the ID, the
authentication code and the cryptographic function
stored in the key module at the terminal device, and

(b) when the communication device is inserted
into the slot, conducting authentication between the
15 communication device and the terminal device, said step
(b) including:

(b-1) collating the ID stored in the
communication device and the ID registered at the
terminal device,

20 (b-2) when collation of IDs succeeds, generating
a random number, sending data obtained by encrypting the
random number with the authentication code connected by
the cryptographic function from the terminal device to
the communication device and at the communication device
25 side, restoring the authentication code and the random
number by the inverse cryptographic function to collate
the restored authentication code and the stored
authentication code, and

(b-3) when collation of authentication codes
30 succeeds, sending data obtained by encrypting said
restored random number by the inverse cryptographic
function from the communication device to the terminal
device and at the terminal device, restoring the random
number by the cryptographic function to collate the
35 restored random number with said random number generated
by the own terminal device.

009227" 8085760

10. The authentication method as set forth in claim 9,
further comprising the step of,

when the communication device is extracted from
the slot after authentication between the terminal
5 device and the communication device is obtained,
bringing the terminal device to a locked state where
none of input by a user is accepted.

11. The authentication method as set forth in claim 9,
further comprising the steps of:

when the communication device is extracted from
the slot after authentication between the terminal
5 device and the communication device is obtained,
bringing the terminal device to a locked state where
none of input by a user is accepted, and

when the communication device is inserted into
the slot of the locked terminal device to obtain
10 authentication between the terminal device and the
communication device, releasing the terminal device from
the locked state.

12. A set of a plurality of communication devices
which can be freely inserted into and extracted from a
slot of a terminal device to wireless-connect terminal
devices, wherein

5 each communication device includes

009221 8085460

a memory readable by said terminal device and storing a communication address of the own communication device and a communication address of other communication device of the same set.

10

13. The set of communication devices as set forth in claim 12, wherein

a common key for data encryption is stored in said memory of each communication device.

5

14. The set of communication devices as set forth in claim 12, wherein

in said memory of each communication device, a secret key of the own communication device and a public key of other communication device of the same set are stored.

5

15. The set of communication devices as set forth in claim 12, wherein

a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

5

10

009227 80854260

16. A set of a plurality of communication devices which can be freely inserted into and extracted from a slot of a terminal device to wireless-connect terminal devices, wherein

5 each communication device includes
a memory readable by said terminal device and storing a communication address of the own communication device and a common key for data encryption inherent to the set.

10 17. The set of communication devices as set forth in claim 16, wherein

5 a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

10 18. A set of a plurality of communication devices which can be freely inserted into and extracted from a slot of a terminal device to wireless-connect terminal devices, wherein

5 each communication device includes
a memory readable by said terminal device and storing a communication address of the own communication

009227 3085460
09745808 122600

device, a public key for data encryption and a secret key for data decoding.

10

19. The set of communication devices as set forth in claim 18, wherein

a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

5

10

20. A method of locally wireless-connecting a plurality of terminal devices by using a set of a plurality of communication devices which can be freely inserted into and extracted from a slot of the terminal device to wireless-connect the terminal devices and which have a memory for storing a communication address of the own communication device, comprising the steps of:

5

(a) allocating a communication device to each of the terminal devices to be wireless-connected,

10

(b) inserting each communication device into a slot of other terminal device than the allocated terminal device to register a communication address stored in the memory of the communication device at a

15 transmission destination list table of the terminal
device into which the communication device is inserted,

(c) inserting each communication device into a
slot of an allocated terminal device, and

(d) by using communication addresses of a
20 transmission destination communication device and a
transmission source communication device as a
transmission destination address and a transmission
source address, transmitting and receiving data between
the terminal devices into which the communication
25 devices are inserted.

21. The wireless-connection method as set forth in
claim 20, wherein

in said memory of each communication device, a
common key inherent to the set is stored, said common
5 key being for use in encryption of transmission data and
decoding of reception data.

22. The wireless-connection method as set forth in
claim 20, wherein

into one slot of a relay device having a
plurality of slots and having a function of relaying
5 data between slots, a communication device of a first
set is inserted and into other one slot, a communication
device of a second set is inserted to enable
communication between a terminal device into which other

09745808 122600

communication device of the first set is inserted and a
terminal device into which other communication device of
the second set is inserted through said relay device.

23. The wireless-connection method as set forth in
claim 20, wherein

a part of the communication device partly
projecting from the terminal device when inserted into
the slot of the terminal device is assigned a number
inherent to the communication device and the
communication address of the communication device is
composed of a high-order address part and a low-order
address part in which part said number is set.

24. The wireless-connection method as set forth in
claim 20, wherein a part of the communication device
partly projecting from the terminal device when inserted
into the slot of the terminal device is assigned a
number inherent to the communication device and the
communication address of the communication device is
composed of a high-order address part and a low-order
address part in which part said number is set.

25. A method of locally wireless-connecting a
plurality of terminal devices by using a set of a
plurality of communication devices which can be freely
inserted into and extracted from a slot of the terminal

009221-8085460

5 device to wireless-connect the terminal devices and
which have a memory for storing a communication address,
a public key and a secret key of the own communication
device, comprising the steps of:

10 (a) allocating a communication device to each of
the terminal devices to be wireless-connected,

(b) inserting each communication device into a
slot of other terminal device than the allocated
terminal device to register a communication address and
a public key stored in the communication device at a
15 transmission destination list table of the terminal
device into which the communication device is inserted,

(c) inserting each communication device into a
slot of an allocated terminal device, and

20 (d) by using communication addresses of a
transmission destination communication device and a
transmission source communication device as a
transmission destination address and a transmission
source address, using a public key of the transmission
destination communication device for the encryption of
25 transmission data and using a secret key for the
decoding of reception data, transmitting and receiving
data between the terminal devices into which the
communication devices are inserted.

26. The wireless-connection method as set forth in
claim 25, wherein

09745808.122600

a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

27. The wireless-connection method as set forth in claim 25, wherein a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

28. A method of locally wireless-connecting a plurality of terminal devices by using a set of a plurality of communication devices which can be freely inserted into and extracted from a slot of the terminal device to wireless-connect the terminal devices and which have a memory for storing a communication address of the own communication device, comprising the steps of:

(a) allocating a communication device to each of the terminal devices to be wireless-connected,

009227" 80854650

(b) into a slot of a specific terminal device, sequentially inserting communication devices allocated to other terminal devices to register communication addresses stored in the communication device at a transmission destination list table of said specific terminal device,

(c) inserting each communication device into a slot of an allocated terminal device,

(d) sequentially transmitting from said specific terminal device to other terminal devices, the contents of said transmission destination list table in which a communication address part of the current transmission destination communication device is replaced by the communication address stored in the communication device inserted into said specific terminal device, and each terminal device at the reception side, setting the contents of the received transmission destination list table at a transmission destination list table of the own device, and

(e) transmitting and receiving data between the terminal devices into which the communication devices are inserted by using communication addresses of a transmission destination communication device and a transmission source communication device as a transmission destination address and a transmission source address.

009221 8085460

29. The wireless-connection method as set forth in claim 28, wherein

in said memory of each communication device, a common key inherent to the set is stored, said common key being for use in encryption of transmission data and decoding of reception data.

30. The wireless-connection method as set forth in claim 28, wherein

into one slot of a relay device having a plurality of slots and having a function of relaying data between slots, a communication device of a first set is inserted and into other one slot, a communication device of a second set is inserted to enable communication between a terminal device into which other communication device of the first set is inserted and a terminal device into which other communication device of the second set is inserted through said relay device.

31. The wireless-connection method as set forth in claim 28, wherein

a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order

009227-8085460

address part in which part said number is set.

32. The wireless-connection method as set forth in claim 28, wherein

a part of the communication device partly projecting from the terminal device when inserted into the slot of the terminal device is assigned a number inherent to the communication device and the communication address of the communication device is composed of a high-order address part and a low-order address part in which part said number is set.

33. A method of locally wireless-connecting a plurality of terminal devices by using a set of a plurality of communication devices which can be freely inserted into and extracted from a slot of the terminal device to wireless-connect the terminal devices and which have a memory for storing a communication address, a public key and a secret key of the own communication device, comprising the steps of:

(a) allocating a communication device to each of the terminal devices to be wireless-connected,

(b) into a slot of a specific terminal device, sequentially inserting communication devices allotted to other terminal devices to register communication addresses and public keys stored in the communication devices at a transmission destination list table of said

specific terminal device,

(c) inserting each communication device into a slot of an allocated terminal device,

(d) sequentially transmitting from said specific terminal device to other terminal devices, the contents of said transmission destination list table in which parts of a communication address and a public key of the current transmission destination communication device are replaced by the communication address and the public key stored in the communication device inserted into said specific terminal device and at the reception side terminal device, setting the contents of the received transmission destination list table at a transmission destination list table of the own device, and

(e) transmitting and receiving data between the terminal devices into which the communication devices are inserted by using communication addresses of a transmission destination communication device and a transmission source communication device as a transmission destination address and a transmission source address, using a public key of the transmission destination communication device for encrypting transmission data and using a secret key for decoding reception data.

34. The wireless-connection method as set forth in claim 33, wherein

09745808.122600

a part of the communication device partly
projecting from the terminal device when inserted into
the slot of the terminal device is assigned a number
inherent to the communication device and the
communication address of the communication device is
composed of a high-order address part and a low-order
address part in which part said number is set.

10

09745808.122600